APPARATI ATTIVI PER TVCC & WLAN

CATV50

(valido dal 14/02/2025)

Modello	Foto	Descrizione	Listino €/cad
Piattaforma CLOUD			
		Piattaforma Cloud per PC	**GRATIS**
Piattaforma CLOUD per cellulare			
		Cloud APP per cellulare	**GRATIS**
Linea prodotti POL (Power Over LAN) NOVITA'			
WI-POL308G-P		*MDU xPON Cloud Managed 8 Ports PoE *1*EPON/GPON SC/UPS *8*1000Mbps IEEE 802.3af/at 30W PoE RJ45 *110W max for whole switch PoE power budget *Support ONVIF protocol *Wi-Tek cloud, OMCI, OAM, WEB management	**290,4 €**
WI-POL5800-08		* Cloud controller for solar powered PoE switch * 4*10GE SFP+ ports * 4*GE ports *8*GPON ports * Abundant L3 functions, it supports RIP, OSPF, BGP,IS-IS etc. helping to build scalable and reliable networks. *1:128 Max splitting ratio *20KM Physical differential distance *Standard OMCI management *Wi-Tek cloud management, provisioning and configuration	**3.210,0 €**
WI-POS132R		* 19" Rack PLC Splitter * 1:32, 1 IN 32 OUT, SC/UPC, SC/APC, LC/APC, LC/UPC connertors are customizable * 16.6dB typical Insertion Loss * 1260~1650 nm Wavelength	**145,2 €**
WI-POS164R		* 19" Rack PLC Splitter * 1:64, 1 IN 64 OUT, SC/UPC, SC/APC, LC/APC, LC/UPC connertors are customizable * 20.1dB typical Insertion Loss * 1260~1650 nm Wavelength	**240,7 €**
WI-POS102B		* 90*20*10mm Mini/ABS Box PLC Splitter * 1:2, 1 IN 2 OUT, SC/UPC, SC/APC, LC/APC, LC/UPC connertors are customizable * 3.6dB typical Insertion Loss * 1260~1650 nm Wavelength	**19,1 €**
WI-POS104B		* 100*80*10mm Mini/ABS Box PLC Splitter * 1:4, 1 IN 4 OUT, SC/UPC, SC/APC, LC/APC, LC/UPC connertors are customizable * 7.0dB typical Insertion Loss * 1260~1650 nm Wavelength	**22,9 €**

WI-POS108B		* 100*80*10mm Mini/ABS Box PLC Splitter * 1:8, 1 IN 8 OUT, SC/UPC, SC/APC, LC/APC, LC/UPC connertors are customizable * 10.2dB typical Insertion Loss * 1260~1650 nm Wavelength	**30,6 €**
WI-SFP51S-20KM-C1		* Class C+ GPON SFP, Rx1.25Gbps/Tx2.5Gbps, SC, 20km,Tx1490/Rx1310, DDM * Optical Transmitter Power: 3~8 dBm * Optical Receiver Sensitivity: -30 dBm	**51,6 €**
WI-SFP51S-20KM-C2		*Class C++ GPON SFP, Rx1.25Gbps/Tx2.5Gbps, , SC, 20km,Tx1490/Rx1310, DDM *Optical Transmitter Power: 4.5~10 dBm *Optical Receiver Sensitivity: -32 dBm	**78,3 €**
Access Point MESH gestibile da Cloud			
WI-AP717MP V2		* AC1200M Indoor Wireless Mesh Wi-Fi *1 WAN+ 2LAN, 3 x Gigabit Ethernet * 11AC Wave2, 2.4GHz 300Mbps+5.8Ghz 887Mbps * MTK chipset 128MB RAM, 16MB Flash, 100mW TX Power, access 60users * 4*5dBi inside antenna * Support 1 x 802.3bt PoE Input+ 2 x 802.3af/at PoE Output * Support Easy Mesh Connect design for big area Wireless Coverage * Support Cloud Managed * 48V 60W Gigabit PoE Adapter Included * Support SD-LAN and open-vpn function （Operating mode: Router Mode)	**188,8 €**
WI-AP718M V2		* Support Easy Mesh protocol, quick mesh link networking. * 1200Mbps Wireless Outdoor Mesh Access Point *1 Gigabit Ethernet PoE ports *300Mbps at 2.4GHz + 867Mbps at 5GHz *Support fast roaming technology *IP65 weatherproof *Support cloud and Web/APP management, internet quick setup.	**329,5 €**
WI-AP719MP		* 802.11AX 2.4G&5.8G 1800M Indoor Wireless Mesh AP * Wi-Fi 6 Speeds: 574Mbps on 2.4GHz +1201Mbps on 5.8Ghz * MTK chipset 128MB DDR3, 16MB Flash, 19dBm Tx Power,access 100users * 4*4dB inside antenna * Support (3)10/100/1000M RJ45 ports * Support 1 PoE Input with 802.3af/at/bt + 2 PoE Output with 802.3af/at * Support Mesh networking design for big area Wireless Coverage * Support Cloud Managed * 48V 30W Gigabit PoE Adapter Included * Support SD-LAN and open-vpn function （Operating mode: Router Mode)	**243,6 €**
Router Mesh WiFi 6 gestibile da Cloud			
WI-AX1800M V2		* 802.11AX 2.4G&5.8G 1800M Indoor Wireless Mesh Router * 11AX 2.4GHz 574Mbps+5.8Ghz 1201Mbps * Atheros chipset 256MB DDR3, 128MB Flash, 300mW High-Power,access 100users * Extensive Coverage: Beamforming, independent FEM, and 4*5dBi antennas combine to deliver focused reception to devices far away * Support Easy Mesh Connect design for big area Wireless Coverage * Support Cloud Managed * Support SD-LAN and open-vpn function	**125,9 €**
Switch Managed L3 PoE gestibile da Cloud			
WI-PCMS528F-L3 V2		*L3 managed Cloud PoE Switch. *24 Gigabit Ethernet RJ-45 PoE+ ports and 4 10G SFP+ slots. *All RJ-45 ports comply with 802.3af/at PoE standard and output up to 30W PoE power per port. 370 W Max PoE power budget. *Abandant L3 management function, supports static routing, RIP, OSPF, DHCP server, DHCP snooping, ACL, ERPS, Spaning tree, QoS policies, Multicast function and diversified VLAN functions. *Support ONVIF device detect. *Cloud Platform Remote Management. Users can view the network status, modify the configuration, and troubleshoot anywhere and anytime.	**967,3 €**
WI-PCMS554F-L3 V2		*L3 managed Cloud PoE Switch. *48 Gigabit Ethernet RJ-45 PoE+ ports and 6 10G SFP+ slots. *All RJ-45 ports comply with 802.3af/at PoE standard and output up to 30W PoE power per port. 370W Max PoE power budget. *Abandant L3 management function, supports static routing, RIP, OSPF, DHCP server, DHCP snooping, ACL, ERPS, Spaning tree, QoS policies, Multicast function and diversified VLAN functions. *Support ONVIF device detect. *Cloud Platform Remote Management. Users can view the network status, modify the configuration, and troubleshoot anywhere and anytime.	**1.397,2 €**

WI-PCMS554FP-L3		* L3 managed Cloud PoE Switch. * New high quality silve case design. * 48 1000Mbps PoE ports and 6 10G SFP+. * 800W Power budget. * Abundant L3 functions, it supports RIP, OSPF, DHCP, etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**1.683,8 €**
WI-CGS5328-L3 V2		* Cloud L3 managed fiber Ethernet Switch. * New high quality silver case design. * 8 1000Mbps Combo SFP, 16 Gigabit SFP ports and 4 10G SFP+. * Abundant L3 functions, it supports RIP, OSPF, DHCP, etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**967,3 €**
WI-CFS6012-L3		* Cloud L3 managed fiber aggregation Switch. * High quality silver case design. * 12 10G SFP+. * Abundant L3 functions, it supports RIP, OSPF, DHCP, etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**788,2 €**
WI-PCMS5010BT-L3		* Cloud L3 managed PoE Switch. * New high quality silver case design. * 8 2.5G 90W 802.3bt PoE ports and 2 10G SFP+. * 130W Power budget. * Abundant L3 functions, it supports RIP, OSPF, DHCP, etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**824,0 €**
Switch Managed L2 PoE gestibile da Cloud			
WI-PCMS310GF V2		* Cloud L2+ managed fiber PoE Switch. * New high quality silver case design. * 8 1000Mbps PoE ports and 2 1000Mbps SFP. * 140W Power budget. * Abundant L2+ functions, it supports static routing, DHCP server, ERPS etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**273,9 €**
WI-PCMS328GF V2		* Cloud L2+ managed fiber PoE Switch. * New high quality silver case design. * 24 1000Mbps PoE ports, 2 1000Mbps SFP and 2 1000Mbps Combo SFP. * 370W Power budget. * Abundant L2+ functions, it supports static routing, DHCP server, ERPS etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**659,0 €**
Switch Managed L2+ gestibile da Cloud			
WI-CMS310GF		* Cloud L2+ managed fiber Ethernet Switch. * New high quality silver case design. * 8 1000Mbps RJ45 ports and 2 1000Mbps SFP. * Abundant L2+ functions, it supports static routing, DHCP server, ERPS etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**218,4 €**
WI-CMS318GF		* Cloud L2+ managed fiber Ethernet Switch. * New high quality silver case design. * 16 1000Mbps RJ45 ports and 2 1000Mbps SFP. * Abundant L2+ functions, it supports static routing, DHCP server, ERPS etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**344,3 €**
WI-CMS328GF		* Cloud L2+ managed fiber Ethernet Switch. * New high quality silver case design. * 24 1000Mbps RJ45 ports, 2 1000Mbps SFP and 2 1000Mbps Combo. * Abundant L2+ functions, it supports static routing, DHCP server, ERPS etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**399,8 €**

Switch Managed L3 gestibile da Cloud			
WI-CMS528F-L3		* Cloud L3 managed Switch. * 24 1000Mbps RJ45 ports and 4 10G SFP+ slots. * Abundant L3 functions, it supports RIP, OSPF, DHCP, etc. helping to build scalable and reliable networks. * Reliable Security Functions: ACL, DHCP Snooping, IP-MAC-Port Binding * Remote management and Configuration on Cloud WEB/Mobile APP.	**436,8 €**
WI-CMS554F-L3		* Cloud L3 managed Switch. * 48 1000Mbps RJ45 ports and 6 10G SFP+ slots. * Abundant L3 functions, it supports RIP, OSPF, DHCP, etc. helping to build scalable and reliable networks. * Reliable Security Functions: ACL, DHCP Snooping, IP-MAC-Port Binding * Remote management and Configuration on Cloud WEB/Mobile APP.	**1.084,7 €**
Switch di aggregazione fibra Managed L2 gestibile da Cloud			
WI-CGS5026 V2		* Cloud L2+ managed fiber Ethernet Switch. * New high quality silver case design. * 8 1000Mbps RJ45 ports and 18 Gigabit SFP. * Abundant L2+ functions, it supports static routing, DHCP server, ERPS etc. helping to build scalable and reliable networks. * Remote management and Configuration on Cloud WEB/Mobile APP.	**609,0 €**
Switch Gigabit Easy Smart Managed PoE gestibile da Cloud			
WI-PCES306G V2		* 6*10/100/1000Mbps RJ45 port Cloud Easy Smart PoE Switch * 4×802.3af/at PoE+ ports, total power supply 60W *Support Wi-Tek Cloud management, configure VLAN, restart POE port, mobile phone APP remote maintenance, various real-time alarms, even novice can troubleshoot. *Support port automatic anti-loop and automatically close loop ports to ensure business continuity. *Support Google map view, let users know the project location, easy to manage *Discover the ONVIF protocol, so that the IP camera can automatically identify the cloud topology map.	**100,0 €**
WI-PCES310G		* Cloud Easy smart full Ggiabit PoE switch. * 8*10/100/1000Mbps RJ45 PoE Ports, 2*1000Mbps RJ45 uplink ports * 8*802.3af/at PoE+ ports, total PoE power of up to 100W * Support Wi-Tek Cloud management for real-time monitoring and remote configuration * Support port automatic anti-loop to ensure network continuity * Support alarm notifications, easy to maintain in real time * Support Onvif protocol to automatically identify IP camera	**162,9 €**
WI-PCES310GF V2		* 8*10/100/1000Mbps RJ45 Ports 2*1000Mbps SFP Slots Cloud Easy Smart PoE Switch * 8×802.3af/at PoE+ ports, total power supply 120W *Support Wi-Tek Cloud management, configure VLAN, restart POE port, mobile phone APP remote maintenance, various real-time alarms, even novice can troubleshoot. *Support port automatic anti-loop and automatically close loop ports to ensure business continuity. *Support Google map view, let users know the project location, easy to manage *Discover the ONVIF protocol, so that the IP camera can automatically identify the cloud topology map.	**185,1 €**
WI-PCES318GF V2		* 16*10/100/1000Mbps RJ45 Ports 2*1000Mbps SFP Slots Cloud Easy Smart PoE Switch * 16×802.3af/at PoE+ ports, total power supply 250W * Support Wi-Tek Cloud management, configure VLAN, restart POE port, mobile phone APP remote maintenance, various real-time alarms, even novice can troubleshoot. * Support port automatic anti-loop and automatically close loop ports to ensure business continuity. * Support Google map view, let users know the project location, easy to manage * Discover the ONVIF protocol, so that the IP camera can automatically identify the cloud topology map.	**407,2 €**
WI-PCES326GF V2		* 24*10/100/1000Mbps RJ45 Ports 2*1000Mbps SFP Slots Cloud Easy Smart PoE Switch * 24×802.3af/at PoE+ ports, total power supply 370W *Support Wi-Tek Cloud management, configure VLAN, restart POE port, mobile phone APP remote maintenance, various real-time alarms, even novice can troubleshoot. * Support port automatic anti-loop and automatically close loop ports to ensure business continuity. *Support Google map view, let users know the project location, easy to manage * Discover the ONVIF protocol, so that the IP camera can automatically identify the cloud topology map.	**525,7 €**

Switch MEGABIT Easy Smart Managed 250m PoE gestibile da Cloud			
WI-PCES206		* Cloud Easy smart PoE Switch. * 4 100Mbps PoE ports and 2 100Mbps RJ45 Uplink. * Port 1: Hi-PoE output, Port 2-4: 802.3at PoE output * 60W PoE Power budget. * Support VLAN, PoE congiguration, Loop Prevention etc. * Remote management and Configuration on Cloud WEB/Mobile APP.	62,9 €
WI-PCES210G		* Cloud Easy smart PoE Switch. * 8 100Mbps PoE ports and 2 1000Mbps RJ45 Uplink. * Port 1-2: Hi-PoE output, Port 3-8: 802.3at PoE output. * 100W PoE Power budget. * Support VLAN, PoE congiguration, Loop Prevention etc. * Remote management and Configuration on Cloud WEB/Mobile APP.	107,4 €
WI-PCES218GF		* Cloud Easy smart PoE Switch. * 16 100Mbps PoE ports and 2 1000Mbps Combo SFP Uplink. * Port 1-2: 802.3bt PoE output, Port 3-16: 802.3at PoE output. * 250W PoE Power budget. * Support VLAN, PoE congiguration, Loop Prevention etc. * Remote management and Configuration on Cloud WEB/Mobile APP.	273,9 €
WI-PCES226GF		* Cloud Easy smart PoE Switch. * 24 100Mbps PoE ports and 2 1000Mbps Combo SFP Uplink. * Port 1-2: 802.3bt PoE output, Port 3-24: 802.3at PoE output. * 280W PoE Power budget. * Support VLAN, PoE congiguration, Loop Prevention etc. * Remote management and Configuration on Cloud WEB/Mobile APP.	359,1 €
CPE da esterno LTE 4G			
WI-LTE110-O V2		* CAT4 4G transform to Wi-Fi(2.4G 300Mbps) and wired network * 1 x 10/100Mbps RJ45 Ports * Build in 3G/4G SIM card slot, support LTE-TDD/LTE-FDD, WCDMA/CDMA and GSM networking. Then band adjustable, can comply with all operator in the world. * High RF power design,with 2dBi omni 4G antenna, better signal strength and more stable performance. * Support 2 power supply: 24V passive PoE or DC12V/1A * Support Cloud Managed and SD-LAN function * Support 4K HD video transmit * Support 10KV Lightning Protection * Support IP65 waterproof	144,4 €
WI-LTE113-O		* CAT6 4G transform to Wi-Fi(2.4G 300Mbps) and wired network, *1 x 10/100/1000 Mbps RJ45 Ports * Build in 3G/4G SIM card slot, support LTE-TDD/LTE-FDD, WCDMA/CDMA and GSM networking. Then band adjustable, can comply with all operator in the world. * with 19 dBi omni 4G antenna, better signal strength and more stable performance. * 4G LTE Cat 6 300 Mbps (DL)/50 Mbps (UL) * Support Cloud Managed and SD-LAN function * 802.3af/at or 24V PoE and Gigabit Ethernet * Support 16KV Lightning Protection * Support IP65 waterproof	473,9 €
WI-LTE117-O V2		* 4G CAT4 + 2.4G 300Mbps Wi-Fi + 2 * 100Mbps RJ45 port * 1* micro SIM slot, support LTE-TDD/LTE-FDD, WCDMA/CDMA and GSM * Support 1*802.3at PoE Input, 1*802.3af PoE Output * Support 48-54V DC Input, 2*802.3af PoE Output * 2*5dBi external 4G antenna, 2*5dBi built-in Wi-Fi antenna. * Support IP65 waterproof * Support Cloud Managed and SD-LAN function * Included 1*48V PoE adapter (Pin 12+ 36-) in packing box	159,2 €
Router da interno Wi-Fi 4G LTE			
WI-LTE300 V2		* CAT4 4G transform to Wi-Fi (2.4G 300Mbps) and wired network * 3 x 10/100Mbps RJ45 Ports * Build in 3G/4G SIM card slot, support LTE-TDD/LTE-FDD, WCDMA/CDMA and GSM networking.Then band adjustable, can comply with all operator in the world. * High RF power design, with omni 2.4G/4G antenna, more wireless coverage, better signal strength and more stable performance. * Support 4K HD video transmit * Support 4G accees, Router mode * Support 30users+ for Wi-Fi access,Wi-Fi Coverage 100meters * Support Cloud Managed and SD-LAN function	99,4 €

Switch PoE solare UPS anti interruzione (Cloud , Managed)			
WI-IOT100		* Cloud controller for solar powered UPS PoE switch * Photovoltaic and battery status real-time and trendline monitor of solar power PoE switch in Wi-Tek cloud * 1*100Mbps IEEE 802.3af PoE IN, 1*100Mbps RJ45 * 1*RS-485 to connect solar powered PoE switch * IEEE 802.3af PoE IN and 12~54V DC power supply * -20~65 °C operating temperature * Included DIN-rail accessories	**82,4 €**
WI-PS306GF-UPS V3		* 5GE+1SFP Unmanaged UPS No-break PoE Switch * 3*48V PoE out(2*30W/1*60W),2*24V/48V Mixed PoE Output(30W) * Inside solar controller and battery controller for 5A charge current Max and dis-charge battery circulatory from solar Panel and DC INPUT * 10hours charge full 12V/24V 50AH lead-acid/lithium battery * Support 15-36V DC IN, 12V/24V Solar Panel Input, 12V/24V Battery 50AH Max * 6KV anti-thunder, small size design for outdoor used * Working temperature -20℃~60℃ * Included 24V 5A Power adapter in packing box	**322,4 €**
BEST SELLER **WI-PS306GF-UPS-15A V2**		New update: RS-485 for WI-IOT100 to cloud management! * 1*1000Mbps IEEE 802.3bt 60W PoE RJ45, 2*1000Mbps IEEE 802.3af/at 30W PoE RJ45, 2*1000Mbps IEEE 802.3af/at 30W PoE or 24V passive 24W PoE RJ45, 1*1000Mbps SFP * 1*RS-485 for WI-IOT100 to cloud management * 2*Photovoltaic input, 1* Battery charging &discharging * 120W max for whole switch PoE power budget * 15A max for battery charging current * Support PoE watchdog, Port VLAN, Extend function * Operating Temperature: -20 ~ 65°C	**348,0 €**
WI-PMS306GF-UPS-I		* 4GE+2SFP L2 managed UPS No-break Industrial PoE Switch * 2*48V PoE out(802.3BT 90W),2*24V/48V Mixed PoE Output(30W) * Inside solar controller and battery controller for 10A charge current Max and dis-charge battery circulatory from solar Panel * 10hours charge full 12V/24V 150AH lead-acid/lithium battery/lifepo4 * Support 12-57V DC IN, 12V/24V Solar Panel Input, 12V/24V Battery 150AH Max * Support monitor battery chargeing status via WEB GUI * Support QVLAN,QoS and IGMP snooping optimize voice and video application * Industrial Level 4 Protection (ESD,RS,EFT,CS) * Support fast ring ,support 30 pcs switches Max. in a cascade system ,Self-healing in 20ms Min * Support DIN-RAIL mounted * Working temperature -40℃~80℃	**621,9 €**
WI-PMS310GF-UPS+ V2		* 8GE+2SFP L2 Managed UPS No-break 24V/48V Auto-detect PoE Switch * 8*24V/48V Mixed PoE Output(30W), Internal 150W power * Inside solar controller and battery controller for 20A charge and dis-charge battery circulatory from solar Panel and AC INPUT * 10hours charge full 12V/24V 200AH lead-acid/lithium battery/lifepo4 * Support QVLAN,QoS and IGMP snooping optimize voice and video application * WEB/CLI,SNMP managed modes * Support 110-250V AC IN, 12-57V Solar Panel , 12/24V Battery 200AH Max * Support monitor battery chargeing status via WEB GUI * Working temperature -20℃~60℃	**696,0 €**
WI-PV200-39		*200W single crystal silicon solar panel, for 12V battery system, applicable to all solar powered PoE switch *Maximum Power Voltage (Vmp)=22.45V *Maximum Power Current (Imp)=8.91A *Open Circuit Voltage (Voc)=26.01V *Short Circuit Current (Isc)=9.41A *1485*668*30mm Dimensions *10.5kg Weight *IP65 *Included solar panel with 2.5mm2 50cm cable, MC4 connector and MC4 Extension Cord (2.5mm2, 100cm, MC4, Without insulation layer at end 0.5cm) for solar powered PoE switch.	**236,9 €**
WI-BRKP133		*Designed for the small-medium pole-mounted solar power application *Suitable for 76~133mm round pole, compatible with a square pole *540mm~900mm adjustable width, 25mm~35m adjustable depth, 0°~50°(0°~50° is recommended, 0~75° max.) adjustable angle for solar panel *SGCC heavy galvanized steel, with baking varnish *Anti-ultraviolet, resist corrosion designed for durability in harsh environments	**277,6 €**

Switch PoE Wi-Fi			
WI-R3		AC1200Mbps Wi-Fi PoE Switch 4* 10/100Mbps RJ45 ports 11AC Wave1 2.4GHz 300Mbps+5.8Ghz 867Mbps Support 3 PoE Output for IPC when PoE Input 48V Support 3 PoE Output for IPC when DC Input 52V 100mW Power Output + 4*5dbi High Gain Antennas Wall penetration wifi design64MB SDRAM 16MB Flash, 600Mhz CPU Included 52V 1.25A DC power adapter in packing box Support Cloud Managed	**62,9 €**
BOX IoT IP65			
WI-IOTBOXMINI		*Housing IP65 and IK10 Deisgn *1.2mm thickness 430 Stainless Steel Material *Included Wall mounting and Pole mounting kits *Included 1*DIN rails for customer equipment *Included 1*DIN Railcircuit breaker, 1*Fan, 1*Microswitch *M25 Waterproof Port connectors*2pcs for RJ45 and AC cable *IPC/Wireless AP mounting hole cover*2pcs *Operating Temperature: -40 ~ 80°C *Dimension: Overall Size300*300*206.5mm, Inner Size 250*250*180mm *Multiple use for Junction, Distribution, Electrical, Batterv, Control, Monitoring etc. Outdoor waterproof Enclosure Box	**318,8 €**
WI-IOTBOX01		* Housing IP65 and IK10 Deisgn * 1.2mm thickness 430 Stainless Steel Material * Included Wall mounting and Pole mounting kits * Included DIN Railcircuit breaker*1pcs * Waterproof Port connectors*4pcs for RJ45 and AC cable * IPC/Wireless AP mounting hole cover*4pcs * Operating Temperature: -40 ~ 80°C; * Dimension: Overall Size 300*400*200mm; Inner Size 250*350*190mm * Multiple use for Junction, Distribution, Electrical, Battery, Control, Monitoring etc. Outdoor waterproof Enclosure Box	**437,1 €**
WI-IOTBOX02		* Housing IP65 and IK10 Deisgn * 1.2mm thickness 430 Stainless Steel Material * Included Wall mounting and Pole mounting kits * Included 3 mounting plate with DIN rails for customer equipment * Included DIN Railcircuit breaker*1pcs * Waterproof Port connectors*4pcs for RJ45 and AC cable * IPC/Wireless AP mounting hole cover*4pcs * Operating Temperature: -40 ~ 80°C * Dimension: Overall Size 400*600*250mm; Inner Size 350*560*240mm * Multiple use for Junction, Distribution, Electrical, Battery, Control, Monitoring etc. Outdoor waterproof Enclosure Box	**580,4 €**
WI-IOTBOX03		*Housing IP65 and IK10 Deisgn *1.2mm thickness 430 Stainless Steel Material *Included Wall mounting and Pole mounting kits *Included 2 fixed mounting plate with DIN rails for customer equipment *Included DIN Railcircuit breaker*1pcs *Waterproof Port connectors*4pcs for RJ45 and AC cable *IPC/Wireless AP mounting hole cover*4pcs *Operating Temperature: -40 ~ 80°C *Dimension: Overall Size 500*700*300mm:Inner Size 450*650*290mm *Multiple use for Junction, Distribution, Electrical, Batterv, Control, Monitoring etc. Outdoor waterproof Enclosure Box	**723,7 €**
WI-IOT110		* CAT4 4G transform to Wi-Fi(2.4G 300Mbps) and wired network * Build in 3G/4G SIM card slot, support LTE-TDD/LTE-FDD, WCDMA/CDMA and GSM networking * 128MB DDR2, 16MB Flash * With 5dBI omni 4G antenna, 2*5dBi WiFi antenna * Support 2 PoE Output for IPC when with Input 48-52V * Integrated 1 RS-485 and 1 RS-232 communication interface * Support 3RD Party IoT PLlatforms, Microsoft Azure and Amazon AWS * Support cloud management * Modbus TCP can be used for transmission to Provides Flexible Network Connectivity for Factory Automation * 1*Digital Input and Digital Output * DC Input 12-60V * Operation temperature: -30 ℃ ~+65℃	**222,1 €**

Switch PoE serie Alien 24-48V			
WI-PMS310GF-Alien		* 8GE+2SFP L2 managed 24V/48V Auto-detect PoE Switch * Support 48V 802.3af/at and 24V Passive PoE both * Wi-Tek Smart PoE Tech support 8*24/48V PoE output via auto-detect and select in software * Support overcurrent protection/short-circuit protection * Internl 150W power,dual PoE voltage output design * Support QVLAN,QoS and IGMP snooping optimize voice and video application * WEB/CLI,SNMP managed modes * Working temperature -10℃～55℃	**348,0 €**
WI-PMS310GF- Alien-I V2		*8GE+2SFP L2 managed industrial 24V/48V Auto-detect PoE Switch *Wi-Tek Smart PoE Tech support 24/48V(30W) PoE output via auto-detect and select in software for Port 3-8 *Support 60W Hi-PoE for Port 1-2 *Buffer reaches 4Mbit, Support 4K high-definition video transmission *Support fast ring, support 30 pcs switches Max. in a cascade system ,Self-healing in 20ms Min *Industrial Level 4 Protection (ESD,RS,EFT,CS); *DC Input 9-52V,can work with Smart Solar Controller *Support DIN-RAIL mounted *Working temperature -40℃～80℃	**680,7 €**
WI-POE60-24V		* 2*1000Mbps RJ45 Ports with 1*48V 802.3af/at PoE IN, 1*24V (30W) PoE Out * Support Passive PoE 24V Output * Support DC 36-60V Input * Delivers power up to 100 meters * Auto-determine the necessary power requirements * Plug-and-Play, no configuration * Short Circuit Protection * Mini Plastic case design * Working temperature -10℃～55℃	**28,1 €**
WI-POE90X		* 2*1000Mbps RJ45 Ports with 1*24V PoE IN, 1*48V 802.3af/at PoE Out * Support 802.3af/at PoE 48V output * Support Passive PoE 24V Input(45+78-) * Support DC 12-57V Input,can work with Smart Solar Controller * Delivers power up to 100 meters * Auto-determine the necessary power requirements * Plug-and-Play, no configuration * Short Circuit Protection * Iron case design * Working temperature -10℃～70℃	**61,1 €**

Switch per esterno Waterproof IP65 con PoE 802.3af/at			
WI-PS306GF-O-DC		* 4GE(PoE out)+1GE(60W PoE in)+1SFP Gigabit Outdoor PoE Switch * Port 1: 10/100/1000Mbps 802.3bt PoE 60W input * Port 2: 10/100/1000Mbps Passive 24V 0.5A PoE output * Port 3-5: 10/100/1000Mbps RJ-45port with 802.3af/at PoE 30W output * IP65 Weatherproof enclosure, -30 ～70℃ working temperature * Support DC Input: DC 48~52V * 65W Power budget Max * 6KV PoE Surge Protection	**159,2 €**
WI-PCES206-O		* IP65 weatherproof new enclosure design. * Cloud Easy smart managed. * 4 100Mbps PoE ports and 2 100Mbps RJ45. * Port 1 : Hi-PoE, Port 2-4: 30W PoE. * Independent DIP switch mode: Extend, VLAN, PD alive. * Support Wi-Tek Cloud management for real-time monitoring and remote configuration. * Support alarm notifications, easy to maintain in real time * Support Onvif protocol to automatically identify IP camera	**107,4 €**
WI-PCES210G-O		* IP65 weatherproof new enclosure design. * Cloud Easy smart managed. * 8 100Mbps PoE ports and 2 1000Mbps RJ45. * Port 1-2 : Hi-PoE, Port 3-8: 30W PoE. * Independent DIP switch mode: Extend, VLAN, PD alive. * Support Wi-Tek Cloud management for real-time monitoring and remote configuration. * Support alarm notifications, easy to maintain in real time * Support Onvif protocol to automatically identify IP camera	**137,0 €**
WI-PCES306G-O		* IP65 weatherproof new enclosure design. * Cloud Easy smart managed. * 4 1000Mbps PoE+ ports and 2 1000Mbps RJ45 uplink. * Port 1-4: 802.3af/at 30W PoE. * Support Wi-Tek Cloud management for real-time monitoring and remote configuration. * Support alarm notifications, easy to maintain in real time * Support Onvif protocol to automatically identify IP camera	**140,7 €**
WI-PCES309GF-O		* Weatherproof new enclosure design. * Cloud Easy smart managed full Gigabit PoE Switch. * 2* 1000Mbps 802.3bt PoE++ ports, 6*802.3at PoE+ ports, 1 *1000Mbps RJ45 and 1 *1000Mbps SFP uplink ports. * Support Wi-Tek Cloud management for real-time monitoring and remote configuration. * Support alarm notifications, easy to maintain in real time * Support Onvif protocol to automatically identify IP camera * Independent DIP switch mode: Extend, VLAN, PD alive.	**233,2 €**
Switch PoE 802.3af/at per TVCC sino 250 m versione ECONOMICA			
WI-PS205H V2		* 4FE+2FE Uplink Ports 250M Long Range PoE Switch with 4PoE Port * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Internal power adapter supply 40W * Support working mode CCTV (250m PoE+Port VLAN) * 2K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	**38,9 €**
WI-PS210H		* 8FE+2FE Uplink Ports 250M Long Range PoE Switch with 8Port PoE * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Internal power adapter supply 65W * Support working mode CCTV (250m PoE+Port VLAN) * 4K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	**53,7 €**
WI-PS518GH		* 16FE+1GE+1Combo SFP Ports 250M Long Range PoE Switch with 16Port PoE * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Internal power adapter supply 150W * Support working mode CCTV (250m PoE+Port VLAN) and VLAN * 8K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	**199,9 €**

WI-PS526GH		* 24FE+1G+1Combo SFP Ports 250M Long Range PoE Switch with 24Port PoE * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Internal power adapter supply 200W * Support working mode VLAN and Extend (250m PoE) * 8K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	266,5 €
WI-PS305GH		* 4GE+1GE Ports 250M Long Range PoE Switch with 4Port PoE * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN) and VLAN * Internal power adapter supply 45W * 4K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	74,0 €
WI-PS308GH V2		* 8GE+2GE Ports 250M Long Range PoE Switch with 8Port PoE * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN) and VLAN * Internal power adapter supply 65W * 4K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	124,0 €
WI-PS309GFH		* 8GE+1GE+1SFP 250M Long Range PoE Switch with 8Port PoE * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN) and VLAN * Internal power adapter supply 65W * 4K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	135,1 €
WI-PS318GFH		* 16GE+2Combo SFP 250M Long Range PoE Switch with 16Port PoE * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN) and VLAN * Internal power adapter supply 200W * 8K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	359,1 €
WI-PS326GFH		* 24GE+2SFP 250M Long Range PoE Switch with 24Port PoE * Supports PoE power up to 30W for each port * Supports PoE IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN) and VLAN * Internal power adapter supply 280W * 8K entry MAC address table with auto-learning and auto-aging * Realtek Switch Chipset guarantee stable performance * Supports smart watchdog function to monitor compliant PD	489,1 €
Switch Hi-PoE 250m Per TVCC con funzione WatchDOG			
WI-PS206S (V2)		* 250m Unmanaged PoE switch * 4 x 100Mbps PoE Ports, 2 x 100Mbps RJ45 Ports. * Port 1 supports Hi-PoE power up to 60W * PoE power budget can be up to 60W * Independent Smart DIP Switch: Extend mode, Port VLAN mode, PoE watchdog.	46,3 €
WI-PS205 V4		* 4FE+2FE uplink 250M Long Range PoE Switch with 4PoE Port * Supports smart watchdog function to monitor compliant PD * Port 1 supports Hi-PoE power up to 60W fit IEEE 802.3bt compliant PDs * Port 2-4 supports PoE 30W fit IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN+QoS) and VLAN * External power adapter supply 65W (included) * Support 250meters Long range PoE Transmit * Support Smart QoS for Video data priority * Realtek Switch Chipset+TI PoE Chipset guarantee stable performance	59,2 €
WI-PS210S (V2)		* 250m Unmanaged PoE switch * 8 x 100Mbps PoE Ports, 2 x 100Mbps RJ45 Ports. * Port 1-2 supports Hi-PoE power up to 60W * PoE power budget can be up to 100W * Independent Smart DIP Switch: Extend mode, Port VLAN mode, PoE watchdog.	59,2 €

BEST SELLER **WI-PS210 V4**	External Power adapter 	* 8FE+2FE uplink 250M Long Range PoE Switch with 8Port PoE * Supports smart watchdog function to monitor compliant PD * Port 1 supports Hi-PoE power up to 60W fit IEEE 802.3bt compliant PDs * Port 2-8 supports PoE 30W fit IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN+QoS) and VLAN * External power adapter supply 108W (included) * Support 250meters Long range PoE Transmit * Support Smart QoS for Video data priority * Realtek Switch Chipset+TI PoE Chipset guarantee stable performance	**90,7 €**
WI-PS210GS (V2)		* 250m Unmanaged PoE switch * 8 x 100Mbps PoE Ports, 2 x 1000Mbps RJ45 Ports. * Port 1-2 supports Hi-PoE power up to 60W * PoE power budget can be up to 100W * Independent Smart DIP Switch: Extend mode, Port VLAN mode, PoE watchdog.	**81,4 €**
BEST SELLER **WI-PS210G V4**		* 8FE+2GE uplink 250M Long Range PoE Switch with 8Port PoE * Supports smart watchdog function to monitor compliant PD * Port 1 supports Hi-PoE power up to 60W fit IEEE 802.3bt compliant PDs * Port 2-8 supports PoE 30W fit IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN+QoS) and VLAN * Internal power adapter supply 120W * Support 250meters Long range PoE Transmit * Support Smart QoS for Video data priority * Realtek Switch Chipset+TI PoE Chipset guarantee stable performance	**105,5 €**
BEST SELLER **WI-PS518G V4**		* 16FE+1GE+1Combo SFP 250M Long Range PoE Switch with 16Port PoE * Supports smart watchdog function to monitor compliant PD * Port 1-2 supports Hi-PoE power up to 60W fit IEEE 802.3bt compliant PDs * Port 3-16 supports PoE 30W fit IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN+QoS) and VLAN * Internal power adapter supply 200W(upgraded) * Support 250meters Long range PoE Transmit * 8K entry MAC address table with auto-learning and auto-aging * Support Smart QoS for Video data priority * Realtek Switch Chipset+TI PoE Chipset guarantee stable performance	**259,1 €**
BEST SELLER **WI-PS526G V4**		* 24FE+ 2Combo SFP 250M Long Range PoE Switch with 24Port PoE * Supports smart watchdog function to monitor compliant PD * Port 1-2 supports Hi-PoE power up to 60W fit IEEE 802.3bt compliant PDs * Port 3-24 supports PoE 30W fit IEEE 802.3af/at compliant PDs * Support working mode CCTV (250m PoE+Port VLAN+QoS) and VLAN * Internal power adapter supply 270W(upgraded) * Support 250meters Long range PoE Transmit * 8K entry MAC address table with auto-learning and auto-aging * Support Smart QoS for Video data priority * Realtek Switch Chipset+TI PoE Chipset guarantee stable performance	**325,8 €**
Switch Gigabit Ethernet			
WI-SG105 (V3)		* 5 100/1000Mbps RJ45 Ethernet ports * Compact Mini case design suitable for more installation space * Plug and play, zero configuration * Supports desktop * Silent operation ideal for noise sensitive environment	**25,1 €**
WI-SG108 (V3)		* 8 100/1000Mbps RJ45 Ethernet ports * Compact case design suitable for more installation space * Plug and play, zero configuration * Supports desktop * Silent operation ideal for noise sensitive environment	**35,8 €**
WI-SG116D V2		* 16xGigabit Desktop Ethernet Switch * Support Port VLAN mode and loop detection * 16 Auto-Negotiation, Auto-MDI/MDIX Ethernet ports provide smart switching * Standard 13-inch Desktop steel case * Plug and Play design simplifies installation * Plans different power output for different cable lengths * Complies with IEEE 802.3, IEEE 802.3u, IEEE 802.3x standards	**118,2 €**
WI-SG124D V2		* 24xGigabit Desktop Ethernet Switch * Support Port VLAN mode and loop detection * 24 Auto-Negotiation, Auto-MDI/MDIX Ethernet ports provide smart switching * Standard 13-inch Desktop steel case * Plug and Play design simplifies installation * Plans different power output for different cable lengths * Complies with IEEE 802.3, IEEE 802.3u, IEEE 802.3x standards	**155,5 €**

WI-SG116F V2		* 16GE+2SFP Full Giga rack-mountable Ethernet Switch * 18 Auto-Negotiation, Auto-MDI/MDIX Ethernet ports provide smart switching * Standard 19-inch rack-mountable steel case * Plug and Play design simplifies installation * Plans different power output for different cable lengths * Complies with IEEE 802.3, IEEE 802.3u, IEEE 802.3x standards * Support Port VLAN mode and QoS	**181,4 €**
WI-SG124F V2		* 24GE+2SFP Full Giga rack-mountable Ethernet Switch * 26 Auto-Negotiation, Auto-MDI/MDIX Ethernet ports provide smart switching * Standard 19-inch rack-mountable steel case * Plug and Play design simplifies installation * Plans different power output for different cable lengths * Complies with IEEE 802.3, IEEE 802.3u, IEEE 802.3x standards * Support Port VLAN mode and QoS	**211,0 €**
Iniettori Poe 2.5 Gigabit/10 Gigabit			
WI-POE65-2.5G-30W		* 2*2.5GE PoE Injector with 2*RJ45 Port * Support camera, wireless AP, and IP phone etc. * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at 30W PoE Out * Plug and play, self-adaption. * AC IN 100-220V	**40,7 €**
WI-POE65-2.5G-60W		* 2*2.5GE PoE Injector with 2*RJ45 Port * Support camera, wireless AP, and IP phone etc. * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at/bt 60W PoE Out * Plug and play, self-adaption. * AC IN 100-220V	**72,2 €**
Switch PoE versione HARDENED Megabit			
BEST SELLER **WI-PS206GF-I V2**		* 4FE+1GE+1SFP Fiber Uplink Hardened PoE Switch with 4Port PoE * Ports 1 : 802.3 af/at/bt 90W, Ports 2-4: 802.3 af/at 30W PoE * Supports smart watchdog function to monitor compliant PD * Support 250meters Long-Range PoE * Support Port VLAN * 6kV surge immunity, 15kV air discharge and 8kV contact discharge ESD protection *-30℃～65℃ working temperature * Support redundant DC Input 48-57V * Support DIN-RAIL mounted * Include Power adapter: 52V 1.25A	**151,8 €**
BEST SELLER **WI-PS212GF-I V2**		* 8FE+1GE+1SFP Fiber Uplink Hardened PoE Switch with 4Port PoE * Ports 1-2 : 802.3 af/at/bt 90W, Ports 3-8: 802.3 af/at 30W PoE * Supports smart watchdog function to monitor compliant PD * Support 250meters Long-Range PoE * Support Port VLAN * 6kV surge immunity, 15kV air discharge and 8kV contact discharge ESD protection *-30℃～65℃ working temperature * Support redundant DC Input 48-57V * Support DIN-RAIL mounted * Include Power adapter: 52V 1.86A (-30~65℃) / 2.3A (0~50℃)	**203,6 €**
Switch Cloud L2 managed PoE di tipo industriale Gigabit			
BEST SELLER **WI-PCMS306GF-I (V2)**		* Cloud L2+ Managed PoE Switch, support DHCP Server, Static Routing, ERPS. * 4*10/100/1000 Base-T PoE+ ports and 2*10/100/1000 Base-X SFP * Ports 1-4: 802.3 af/at PoE * Easily remote manage your ONVIF camera via the Wi-Tek Cloud platform/ mobile APP. * -40℃~75℃ operating temperature * 6kV surge immunity and 8kV ESD protection * Not include power adapter	**418,3 €**
WI-PCMS310GF-I (V2)		* Cloud L2+ Managed PoE Switch, support DHCP Server, Static Routing, ERPS. * 8*10/100/1000 Base-T PoE+ ports and 2*10/100/1000 Base-X SFP * Ports 1-8: 802.3 af/at PoE * Easily remote manage your ONVIF camera via the Wi-Tek Cloud platform/ mobile APP. * -40℃~75℃ operating temperature * 6kV surge immunity and 8kV ESD protection * Not include power adapter	**555,3 €**

WI-PCMS312GF-BT-I (V2)		* Cloud L2+ Managed PoE Switch, support DHCP Server, Static Routing, ERPS. * 8*10/100/1000 Base-T PoE++ ports and 4*10/100/1000 Base-X SFP * Ports 1-8: 802.3 af/at/bt 90W PoE * Easily remote manage your ONVIF camera via the Wi-Tek Cloud platform/ mobile APP * -40℃~75℃ operating temperature * 6kV surge immunity and 8kV ESD protection * Not include power adapter	**659,0 €**
WI-RSC302PD		* 1000Mbps PoE to 1000Mbps SFP converter * IEEE 802.3af/at PoE IN * 9/12/24/48V DC@18W max OUT * Dimension: 55mm*54mm*41mm * DIN-Rail Installation	**59,2 €**
Switch Industriali PoE piatti e a badda DIN			
WI-PCES310GF-F		* Industrial Flat-type Switch. * Cloud Easy smart PoE Switch. * 8 1000Mbps PoE ports and 2 1000Mbps SFP. * Port 1-2 support 802.3bt PoE. * -40~75℃ operating temperature, 6kV surge immunity and 8kV ESD protection. * Support magnetic mounting, DIN-rail mounting installation. * Support VLAN, Link aggregation, PoE congiguration, Loop Prevention etc. * Remote management and Configuration on Cloud WEB/Mobile APP.	**470,0 €**
WI-PS305G-F-M12 ***(Prototipo susponibile in 12 settimane)***		* Industrial M12 Gigabit PoE+ Switch * 4 x M12 (X-code) Gigabit PoE+ ports, 1 x M12 (X-code) Gigabit port, 1 x M12 (A-code) power port * M12 interfaces design protects against vibration effects for moving bus, train, and other rolling stock applications. * IP67 waterproof enclosure design, meet the outdoor harsh environment * Operating temperature range of -40° – 75° C * Support wall mounting and DIN-rail mounting * Not include power adapter * EN 50155 Compliance,is certified for railway and rolling stock applications	**999,5 €**
WI-PS310G-F-M12 ***(Prototipo disponibile in 12 settimane)***		* Industrial M12 Gigabit PoE+ Switch * 8 x M12 (X-code) Gigabit PoE+ ports, 2 x M12 (X-code) Gigabit port with Bypass function,1 x M12 (A-code) power port * M12 interfaces design protects against vibration effects for moving bus, train, and other rolling s● Operating temperature range of -40° – 75° C * Support wall mounting * Not include power adapter * EN 50155 Compliance,is certified for railway and rolling stock applications	**1.739,9 €**
Switch Industriali PoE serie SUPERIC			
SP3006F		* 4GE+2SFP Fiber Uplink Unmanaged Industrial PoE Switch with 4Port PoE * Port 1-4 Support 802.3af/at 30W PoE * Smart DIP Switch: VLAN/Extend/QoS/PoE Watchdog mode * Industrial Level 4 protection(ESD,RS,EFT,CS); * -40℃～75℃ working temperature * 6kV Surge Immunity * Support redundant DC 44~57V power input * Support DIN-RAIL mounted	**214,7 €**
SP3010F		* 8GE+2SFP Fiber Uplink Unmanaged Industrial PoE Switch with 8Port PoE * Port 1-8 Support 802.3af/at 30W PoE * Smart DIP Switch: VLAN/Extend/QoS/PoE Watchdog mode * Industrial Level 4 protection(ESD,RS,EFT,CS); * -40℃～75℃ working temperature * 6kV Surge Immunity * Support redundant DC 44~57V power input * Support DIN-RAIL mounted	**322,1 €**
SP3018F		*16GE+2SFP Fiber Uplink Unmanaged Industrial PoE Switch with 8Port PoE * Port 1-8 Support 802.3af/at 30W PoE * Smart DIP Switch: Link Aggregation/VLAN/Extend/QoS/PoE Watchdog mode * Industrial Level 4 protection(ESD,RS,EFT,CS); * -40℃～75℃ working temperature * 6kV Surge Immunity * Support redundant DC 44~57V power input * Support DIN-RAIL mounted	**733,0 €**

SP3006FM		* 4GE+2SFP Fiber Uplink Easy Smart Managed Industrial PoE Switch with 4Port PoE * Port 1-4 Support 802.3af/at 30W PoE * Support easy smart managed functions, such as VLAN, port mirroring, STP, RSTP, IGMP, QoS, LLDP, 802.1X, fiber transceiver DDM, PoE management, G.8032 ERPS protocol, IPV6 management, Web, SNMP, Telnet, TFTP, etc. * Industrial Level 4 protection(ESD,RS,EFT,CS); * -40℃～75℃ working temperature * 6kV Surge Immunity * Support redundant DC 44~57V power input * Support DIN-RAIL mounted	**325,8 €**
SP3010FM		* 8GE+2*2.5G SFP Fiber Uplink Easy Smart Managed Industrial PoE Switch with 8Port * Port 1-8 Support 802.3af/at 30W PoE * Support easy smart managed functions, such as VLAN, port mirroring, STP, RSTP, IGMP, QoS, LLDP, 802.1X, fiber transceiver DDM, PoE management, G.8032 ERPS protocol, IPV6 management, Web, SNMP, Telnet, TFTP, etc. *Industrial Level 4 protection(ESD,RS,EFT,CS); *-40℃～75℃ working temperature *6kV Surge Immunity *Support redundant DC 44~57V power input *Support DIN-RAIL mounted	**436,8 €**
SP3006FM-L2 V2		* 4GE+2*2.5G SFP Fiber Uplink L2 Managed Industrial PoE Switch with 4Port PoE * Port 1-2: 802.3bt 90W PoE, Port 3-8: 802.3af/at 30W PoE. * Support L2 managed functions, such as VLAN, VLAN classification, QinQ, port mirroring, STP, RSTP, MSTP, IGMP, QoS, DHCP, multicast, ACL, dying gasp, LLDP, 802.1X, fiber transceiver DDM, PoE management, G.8032 ERPS protocol, IPV6 management, Web, SNMP, Telnet, TFTP, etc. *Industrial Level 4 protection(ESD,RS,EFT,CS); *-40℃～75℃ working temperature *6kV Surge Immunity *Support redundant DC 44~57V power input *Support DIN-RAIL mounted	**418,3 €**
SP3010FM-L2 V2		* 8GE+2*2.5G SFP Fiber Uplink L2 Managed Industrial PoE Switch with 8Port PoE * Port 1-2: 802.3bt 90W PoE, Port 3-8: 802.3af/at 30W PoE. * Support L2 managed functions, such as VLAN, VLAN classification, QinQ, port mirroring, STP, RSTP, MSTP, IGMP, QoS, DHCP, multicast, ACL, dying gasp, LLDP, 802.1X, fiber transceiver DDM, PoE management, G.8032 ERPS protocol, IPV6 management, Web, SNMP, Telnet, TFTP, etc. *Industrial Level 4 protection(ESD,RS,EFT,CS); *-40℃～75℃ working temperature *6kV Surge Immunity *Support redundant DC 44~57V power input *Support DIN-RAIL mounted	**547,9 €**
SP3012FM-L2 V2		*L2 managed PoE switch *8*10/100/1000 Base-T PoE+ RJ-45 ports and 4*1000/2500 Base-X SFP slot * Port 1-2: 802.3bt 90W PoE, Port 3-8: 802.3af/at 30W PoE. (Not include power adapter) *Support robust L2 managed function, such as such as VLAN, VLAN classification, QinQ, port mirroring, STP, RSTP, MSTP, IGMP, QoS, DHCP, multicast, ACL, dying gasp,LLDP, 802.1X, fiber transceiver DDM, PoE management, G.8032 ERPS protocol, IPv6 management * - 40℃~75℃ operating temperature * 6kV surge immunity for power and Ethernet ports	**621,9 €**
SP5012FM-L2		*L2 managed PoE switch *8*10/100/1000 Base-T PoE+ RJ-45 ports and 4*1G/2.5G/10G Base-X SFP+Base-X SFP slot *Complies with IEEE 802.3af/at 30W PoE standard, 240W PoE budget max (Not include power adapter) *Support robust L2 managed function, such as such as VLAN, VLAN classification, QinQ, port mirroring, STP, RSTP, MSTP, IGMP, QoS, DHCP, multicast, ACL, dying gasp,LLDP, 802.1X, fiber transceiver DDM, PoE management, G.8032 ERPS protocol, IPv6 management * - 40℃~75℃ operating temperature * 6kV surge immunity for power and Ethernet ports	**770,0 €**
SP3018FM-L2		*L2 managed PoE switch *16*10/100/1000 Base-T PoE+ RJ-45 ports and 2*1000/2500 Base-X SFP slot *Complies with IEEE 802.3af/at 30W PoE standard, 240W PoE budget max (Not include power adapter) *Support robust L2 managed function, such as such as VLAN, VLAN classification, QinQ, port mirroring, STP, RSTP, MSTP, IGMP, QoS, DHCP, multicast, ACL, dying gasp,LLDP, 802.1X, fiber transceiver DDM, PoE management, G.8032 ERPS protocol, IPv6 management * - 40℃~75℃ operating temperature * 6kV surge immunity for power and Ethernet ports	**1.029,1 €**

SP3006F-BT		* Unmanaged Industrial PoE++ switch * 4×10/100/1000 Base-T PoE++ and 2×1000 Base-X SFP ports * Port1-4 Complies with IEEE 802.3af/at/bt 90W PoE standard * Smart DIP Switch ： VLAN/Extend/QoS/PoE Watchdog * - 40℃~75℃ operating temperature * 6kV surge immunity for power and Ethernet ports	**288,8 €**
SP3010F-BT		* Unmanaged Industrial PoE++ switch * Port 1-4: 10/100/1000 Base-T PoE++, Port5-8: 10/100/1000 Base-T PoE+ and 2×1000 Base-X SFP ports * Port 1-4 Complies with IEEE 802.3af/at/bt 90W PoE standard * Smart DIP Switch: VLAN/Extend/QoS/PoE Watchdog * - 40℃~75℃ operating temperature * 6kV surge immunity for power and Ethernet ports	**399,8 €**
S5028FM-16S8C4X-L3		* 16*100/1000Mbps SFP, 8*1000Mbps Combo SFP, 4*1G/2.5/10GG SFP+ * AC/DC redundant power supply with polarity reverse/over-voltage/over-current protection * Abundant Layer 3 features: Supports static and dynamic routing, RIP, OSPF, BGP4, ECMP, VRRP. * Support ERPS protocol.Redundant Ring network, auto network recovery, enhance network reliability . * Industrial-level protection -40~75℃ and 6kV surge protection, 15kV ESD protection. * Quiet fan-less and rack-mount hardware design. * Operation temperature: -40 ℃ ~+ 75℃.	**2.517,3 €**
S5028FM-16T8C4X-L3		* 16* 10/100/1000Mbps RJ45, 8*1000Mbps Combo SFP, 4*1G/2.5/10G SFP+ * AC/DC redundant power supply with polarity reverse/over-voltage/over-current protection * Abundant Layer 3 features: Supports static and dynamic routing, RIP, OSPF, BGP4, ECMP, VRRP. * Support ERPS protocol.Redundant Ring network, auto network recovery, enhance network reliability . * Industrial-level protection -40~75℃ and 6kV surge protection, 15kV ESD protection. * Quiet fan-less and rack-mount hardware design. * Operation temperature: -40 ℃ ~+ 75℃.	**2.369,3 €**
WI-VB102-52V		Voltage Booster, the golder partner for low-voltage power system, such as solar power or 12V/ 24V DC power adapter. Support 1*12-48V DC input. support 2* 52V DC output. Provide the 52V DC for PoE Industrial switch. 12V DC input: 60W output max, 24/48V DC input: 120W max.	**118,5 €**
802.3BT 90W PoE Switch - PoE Injector - PoE Splitter			
WI-POE58-BT V2		* 1*100/1000/2500Mbps PoE output port with 802.3bt 90W * 1*100/1000/2500Mbps Ethernet input port * AC IN 100-240V * An ideal solution for all of high-speed devices, such as Wi-Fi 6/7 AP * Metal casing with high quality * Support desktop and wall mount * Plug and play, zero configuration	**97,4 €**
WI-POE58-BT-I-DC		* 1GE BT 90W PoE+1GE Uplink Industrial PoE Injector * Support camera, wireless AP, and IP phone etc. * All ports support wire speed switch, jumbo frame transmission. * Support 802.3 af/at/bt standard 90W PoE Output * industrial Level 4 Protection (ESD,RS,EFT,CS); *-40℃～80℃ working temperature * DC Input 12-57V,can work with Smart Solar Controller * Support DIN-RAIL mounted	**162,9 €**
WI-POE55S-BT-I-DC		* 1GE(BT 90W PD)+1GE Uplink PoE Splitter * DC output 12V/16V/24V/48V by DIP select * 48-55V PoE IN Comply to IEEE802.3af/at/bt,90W Max * Plug and play, self-adaption. * Built-in high performance chip and high specification circuit board * Support DIN-RAIL mounted	**122,2 €**

Iniettori/Estensori/Divisori Industriali PoE IP68 Waterproof			
WI-POE21E-O		*2GE PoE Output(802.3af/at 30W)+1GE PoE Input(802.3bt 60W) PoE Extender * PoE Output Support 100meter long-Range PoE transmit * All ports support wire speed switch, jumbo frame transmission. * Outdoor IP68 Waterproof design * Industrial Level 4 protection(ESD,RS,EFT,CS); * -40℃～80℃ working temperature * Plug and play, self-adaption.	140,7 €
WI-POE22E-O		*2GE PoE Output(1*802.3af/at 30W+1*802.3af/at 60W)+1GE PoE Input(802.3bt 90W) PoE Extender * PoE Output Support 100meter long-Range PoE transmit * All ports support wire speed switch, jumbo frame transmission. * Outdoor IP68 Waterproof design * Industrial Level 4 protection(ESD,RS,EFT,CS); * -40℃～80℃ working temperature; * Plug and play, self-adaption.	218,4 €
WI-POE56-60W-I-O		* 1GE PoE Output (802.3bt 60W)+1GE Ethernet port+1* DC INPUT 24~56V/3A Max PoE Injector * Support camera, wireless AP, and IP phone etc. * Outdoor IP68 Waterproof design * Industrial Level 4 protection(ESD,RS,EFT,CS); * -40℃～80℃ working temperature; * Plug and play, self-adaption.	236,9 €
WI-POE56S-BT-I-O		*1GE PoE Input (802.3af/at/bt 90W)+1GE Ethernet Output port+1* DC Output 12V/5A Max PoE Splitter * Support camera, wireless AP, and IP phone etc. * Outdoor IP68 Waterproof design * Industrial Level 4 protection(ESD,RS,EFT,CS); * -40℃～80℃ working temperature; * Plug and play, self-adaption.	187,2 €
Iniettori , Splitter ed Estensoti PoE			
WI-POE31-48V		* 2FE PoE Injector with 2*RJ45 Port * Support camera, wireless AP, and IP phone etc. * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at PoE Out * Plug and play, self-adaption. * AC IN 100-220V	17,0 €
WI-POE51-48V V2		* 2GE PoE Injector with 2*RJ45 Port * Support camera, wireless AP, and IP phone etc. * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at PoE Out * Plug and play, self-adaption. * AC IN 100-220V	34,8 €
WI-POE31-24V		* 2FE PoE Injector with 2*RJ45 Port * Support Ubnt,Mikrotik,Cambium, Wi-Tek brand CPE etc * All ports support wire speed switch, jumbo frame transmission. * Support 24V PoE Out(PoE PIN 45+ 78-) * Plug and play, self-adaption. * AC IN 100-220V	17,0 €
WI-POE51-24V		* 2GE PoE Injector with 2*RJ45 Port * Support Ubnt,Mikrotik,Cambium, Wi-Tek brand CPE etc. * All ports support wire speed switch, jumbo frame transmission. * Support 24V PoE Out(PoE PIN 45+ 78-) * Plug and play, self-adaption. * AC IN 100-220V	32,6 €
WI-POE55-48V-60W		* 2GE PoE Injector with 2*RJ45 Port (60W) * Support camera, wireless AP, and IP phone etc. * All ports support wire speed switch, jumbo frame transmission. * Support Hi-PoE standard 60W PoE Output * Plug and play, self-adaption. * AC IN 100-220V	53,7 €

WI-POE11S-48V		* Single 100Mbps fast PoE Splitter with 2*RJ45 Port * DC output 12V 1A * 48V PoE IN Comply to IEEE802.3af/at * Support camera, wireless AP, and IP phone etc. * All ports support wire speed switch, jumbo frame transmission. * Powered by 802.3af/at PoE device * Plug and play, self-adaption. * Built-in high performance chip and high specification circuit board	**9,0 €**
WI-POE31S		* Single Gigabit Industrial PoE Splitter with 2*RJ45 Port * DC output 12V 2.5A * 48V PoE IN Comply to IEEE802.3af/at * Support camera, wireless AP, and IP phone etc. * All ports support wire speed switch, jumbo frame transmission. * Powered by 802.3af/at PoE device * Plug and play, self-adaption. * Built-in high performance chip and high specification circuit board	**48,4 €**
WI-PE21E		* 1FE PoE Output+1FE PoE Input 100Mbps PoE Extender * PoE Output Support 100meter long-Range PoE transmit * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at 30W PoE Input and Output * Mini Plastic case design * DC Input 37-57V	**31,5 €**
WI-PE31E		* 2FE PoE Output+1FE PoE Input 100Mbps PoE Extender * PoE Output Support 250meter long-Range PoE transmit by DIP switch * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at 30W PoE Input and Output * Plug and play, self-adaption. * DC Input 48-55V	**38,9 €**
WI-PE51E		* 4FE PoE Output+1FE PoE Input +1FE Uplink port 100Mbps PoE Extender * PoE Output Support 250meter long-Range PoE transmit by DIP switch * PoE Input port support 60W Hi-PoE * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at 30W PoE Output * Plug and play, self-adaption. * DC Input 48-55V	**61,1 €**
WI-PE21G		* 1GE PoE Output+1GE PoE Input Gigabit PoE Extender * PoE Output Support 100meter long-Range PoE transmit * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at 30W PoE Input and Output * Mini Plastic case design * DC Input 37-57V	**43,9 €**
WI-PE31G		* 2GE PoE Output+1GE PoE Input Gigabit PoE Extender * PoE Output Support 250meter long-Range PoE transmit by DIP switch * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at 30W PoE Input and Output * Plug and play, self-adaption. * DC Input 48-55V	**55,4 €**
WI-PE51G		* 4GE PoE Output+1GE PoE Input PoE Extender * PoE Output Support 250meter long-Range PoE transmit by DIP switch * PoE Input port support 90W Hi-PoE * All ports support wire speed switch, jumbo frame transmission. * Support 802.3af/at 30W PoE Output * Plug and play, self-adaption. * DC Input 48-55V	**84,1 €**

Moduli SFP Gigabit per fibra e rame			q.tà	prezzo
WI-SFP10SC-3KM ***(venduti a coppie)***		* 3KM 1.25Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP SFP * Distance up to 3km over SMF * Simplex SC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**40,7 €**	
WI-SFP10LC-3KM ***(venduti a coppie)***		* 3KM 1.25Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP SFP * Distance up to 3km over SMF * Simplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**37,0 €**	
WI-SFP10SC-20KM ***(venduti a coppie)***		* 20KM 1.25Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP/DFB SFP * Distance up to 20km over SMF * Simplex SC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**44,4 €**	
WI-SFP10LC-20KM ***(venduti a coppie)***		* 20KM 1.25Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP/DFB SFP * Distance up to 20km over SMF * Simplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**44,4 €**	
WI-SFP20-20KM		* 20KM 1.25Gbps Single module Double Fiber Transceivers * Tx1310nm//Rx1310nm DDM SFP * Distance up to 20km over SMF * Duplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**22,2 €**	
WI-SFP20-2.5G-20KM		* 20KM 2.5Gbps Single module Double Fiber Transceivers * Tx1310nm//Rx1310nm DDM SFP * Distance up to 20km over SMF * Single-mode SFP+ LC Transceiver * Compatible with 2.5G Small Form Pluggable Multi-Source Agreement * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**29,6 €**	
WI-SFP10LC-2.5G-20KM ***(venduti a coppie)***		* 20KM 2.5Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP/DFB SFP * Distance up to 20km over SMF * Simplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**59,2 €**	
WI-SFP20-10G-20KM		* 20KM 10Gbps Single module Double Fiber Transceivers * Tx1310nm//Rx1310nm DDM SFP * Distance up to 20km over SMF * Single-mode SFP+ LC Transceiver * Compatible with 10G Small Form Pluggable Multi-Source Agreement (SFP+ MSA) * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**40,7 €**	
WI-SFP10LC-10G-20KM ***(venduti a coppie)***		* 20KM 2.5Gbps Single module Single Fiber Transceivers * Tx1270nm/Rx1330nm and Tx1330nm/Rx1270nm FP/DFB SFP * Distance up to 20km over SMF * Simplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**96,3 €**	

WI-SFP21L-550		* 550M 1.25Gbps Multi module Double Fiber Transceivers * Tx850nm//Rx850nm DDM SFP * Distance up to 550M over SMF * Single-mode SFP+ LC Transceiver * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**22,2 €**
WI-SFP30		* 100meters Copper RJ45 SFP Transceivers * Compliant with IEEE 802.3ab/ Gigabit Ethernet Standard * Distance up to 100meters up 1Gbps Spped * 10/100/1000BASE-T with SGMII interface * Compliant with SFP MSA * Supports MDIX * Hot-pluggable SFP footprint * Operating Temperature: 0℃~70℃	**33,3 €**
WI-SFP30-10G		* Support 10GBASE-T, 5GBASE-T, 2.5GBASE-T, 1000BASE-T, and 100BASE-TX * Transmit data up to 30meters at 10 Gbps (UTP cat.6a or above) * Support DDM (Temperature and Voltage) * Hot-Pluggable SFP+ Footprint Features * Support TX Disable function * Fully Metallic Enclosure for Low EMI * Operating Temperature: 0℃~70℃	**103,9 €**
Moduli SFP fibra e rame per applicazioni Industriali			
WI-SFP30-10G-I		* Support 10GBASE-T, 5GBASE-T, 2.5GBASE-T, 1000BASE-T, and 100BASE-TX * Transmit data up to 30meters at 10 Gbps (UTP cat.6a or above) * Support DDM (Temperature and Voltage) * Hot-Pluggable SFP+ Footprint Features * Support TX Disable function * Fully Metallic Enclosure for Low EMI * Operating Temperature:-40~85℃	**132,6 €**
WI-SFP30-I		* 100meters Copper RJ45 SFP Transceivers * Compliant with IEEE 802.3ab/ Gigabit Ethernet Standard * Distance up to 100meters up 1Gbps Spped * 10/100/1000BASE-T with SGMII interface * Compliant with SFP MSA * Supports MDIX * Hot-pluggable SFP footprint * Operating Temperature:-40~85℃	**50,2 €**
WI-SFP20L-2.5G-20KM-I		* 20KM 2.5Gbps Single module Double Fiber Transceivers * Tx1310nm//Rx1310nm DDM SFP * Distance up to 20km over SMF * Single-mode SFP+ LC Transceiver * Compatible with 2.5G Small Form Pluggable Multi-Source Agreement * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature:-40~85℃	**37,0 €**
WI-SFP10L-2.5G-20KM-I ***(venduti a coppia)***		* 20KM 2.5Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP/DFB SFP * Distance up to 20km over SMF * Simplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: -40~85℃	**68,1 €**
WI-SFP20L-10G-20KM-I		* 20KM 10Gbps Single module Double Fiber Transceivers * Tx1310nm//Rx1310nm DDM SFP * Distance up to 20km over SMF * Single-mode SFP+ LC Transceiver * Compatible with 10G Small Form Pluggable Multi-Source Agreement (SFP+ MSA) * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature:-40~85℃	**53,7 €**
WI-SFP10L-10G-20KM-I ***(Venduti a coppia)***		* 20KM 10Gbps Single module Single Fiber Transceivers * Tx1270nm/Rx1330nm and Tx1330nm/Rx1270nm FP/DFB SFP * Distance up to 20km over SMF * Simplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: -40~85℃	**103,7 €**

WI-SFP21L-550-I		* 550M 1.25Gbps Multi module Double Fiber Transceivers * Tx850nm//Rx850nm DDM SFP * Distance up to 550M over SMF * Single-mode SFP+ LC Transceiver * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: -40~85℃	**28,7 €**
WI-SPF20L-20KM-I		* 20KM 1.25Gbps Single module Double Fiber Transceivers * Tx1310nm//Rx1310nm DDM SFP * Distance up to 20km over SMF * Duplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: -40~85℃	**28,7 €**
WI-SFP10L-20KM-I ***(venduti a coppia)***		* 20KM 1.25Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP/DFB SFP * Distance up to 20km over SMF * Simplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: -40~85℃	**50,2 €**
WI-SFP10L-3KM-I ***(venduti a coppia)***		* 3KM 1.25Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP SFP * Distance up to 3km over SMF * Simplex LC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: -40~85℃	**43,0 €**
WI-SFP10S-20KM-I ***(venduti a coppia)***		* 20KM 1.25Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP/DFB SFP * Distance up to 20km over SMF * Simplex SC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature: -40~85℃	**50,2 €**
WI-SFP10S-3KM-I ***(venduti a coppia)***		* 3KM 1.25Gbps Single module Single Fiber Transceivers * Tx1310nm/Rx1550nm and Tx1550nm/Rx1310nm FP SFP * Distance up to 3km over SMF * Simplex SC connector * Compliant with SFP MSA * Digital Diagnostic Monitoring * Hot-pluggable SFP footprint * Operating Temperature:-40~85℃	**43,0 €**

Antenne CPE Wireless per Lunghe distanze impianti TVCC IP			
WI-CPE110-KIT **(vendute a coppia)**		2.4GHz 300Mbps 1km Wireless Transmitter for CCTV 1* 10/100Mbps WAN (PoE IN) RJ45 port 1* 10/100Mbps LAN RJ45 port With double polarized 65 degrees antenna with 8dBi 21dBm(128mW) adjustable transmission power Durable IP65 ingress protection enclosure along with 8kV ESD Support 24V PoE and 12V DC Input Support 2.412GHz~2.484GHz Channel Pre-configuration by factory for PTP application Support Cloud Managed Discovery ONIVF IP camera and view network topology on Cloud Included 24V PoE power adapter in packing box	**100,0 €**
WI-CPE111-KIT V2 ***(vendute a coppia)***		* 2.4G 300M 2KM Wireless CPE for CCTV * 2KM wireless transmit for Carry 16pcs camera Max * Built-in 2×2 dual-polarized directional MIMO 8dBi antenna * 24V passive PoE Adapter Included * 2.412GHz – 2.484GHz Extension Channel * auto-connect for PTP application, no need setting software * Support google Map view to let users know project location for easy management * Discovery ONVIF IP camera and view network topology on Cloud	**155,5 €**
WI-CPE511H-KIT ***(vendute a coppia)***		* 5.8G 3KM 900M Wireless CPE for CCTV * 3KM wireless transmit for Carry 26pcs camera Max * Built-in 2×2 dual-polarized directional MIMO 12dBi antenna * 24V passive PoE Adapter Included * 5.150GHz～5.850GHz Extension Channel * auto-connect for PTP application, no need setting software * Support google Map view to let users know project location for easy management * Discovery ONVIF IP camera and view network topology on Cloud	**181,4 €**
WI-CPE513P-KIT V3 ***(vendute a coppia)***		* 5.8G 5KM 300M Wireless CPE for CCTV * 5KM wireless transmit for Carry 26pcs camera Max * Built-in 2×2 dual-polarized directional MIMO 13dBi antenna * 802.3af/at PoE Passthrough,can power up camera directly * 48V 802.3af/at PoE Adapter Included, support 1PoE output for IPC * 5.150GHz～5.850GHz Extension Channel * auto-connect for PTP application, no need setting software * Support google Map view to let users know project location for easy management * Discovery ONVIF IP camera and view network topology on Cloud	**270,2 €**
WI-CPE515H-KIT ***(vendute a coppia)***		* 5.8G 8KM 300M Wireless CPE for CCTV * 8KM wireless transmit for Carry 30pcs camera Max * Built-in 2×2 dual-polarized directional MIMO 16dBi antenna * 24V passive PoE Adapter Included * 5.150GHz～5.850GHz Extension Channel * auto-connect for PTP application, no need setting software * Support google Map view to let users know project location for easy management * Discovery ONVIF IP camera and view network topology on Cloud	**236,9 €**
WI-CPE800-KIT V3 ***(vendute a coppia)***		* 5GHz 867Mbps 5km Wireless Transmitter for CCTV * 1* 10/100/1000Mbps WAN (af PoE IN) RJ45 port and 1* 10/100/1000Mbps LAN RJ45 port * With double polarized 33° degrees antenna with 15dBi * 24dBm adjustable transmission power * Support IEEE802.3af PoE and 12V DC Input * Durable IP65 ingress protection enclosure along with 8kV ESD * Pre-configuration by factory for PTP application * Support Cloud Managed * Discovery ONIVF IP camera and view network topology on Cloud * Included 48V PoE power adapter in packing box	**329,5 €**
WI-CPE821		*360° 5GHz 867Mbps 2km Wireless Transmitter for PTMP CCTV network *1* 1000Mbps PoE IN RJ45 port,Support 802.3af/at PoE input *With double polarized 360 degrees antenna with 12dBi *26dBm adjustable transmission power *Durable IP65 ingress protection *Support one key fast paired *Support 5.180GHz~5.825GHz 20/40/80MHz channel bandwidth * Support Wi-Tek Cloud management for real-time monitoring and remote configuration. *Discovery ONIVF IP camera and view network topology on Cloud *Included 48V PoE power adapter in packing box	**436,8 €**

WI-CPE517 V2		* Support Clould Managed * 802.11N 5.8Ghz Sector Antenna 300M 5KM Outdoor Wireless CPE * 500mW High power output, coverage up to 5KM for PTP and PTMP Station application * Wireless A/N speed up to 300Mbps * Integrate 16dBi 150 degree Sector antenna * Support 5.150GHz～5.850GHz Channel * 6KV Lightning Protection	**259,1 €**
WI-BRKC135		*Designed for the small-medium pole-mounted CPE application *Support wall-mounted, square, and round pole-mounted *-45°~+25° adjustable angle for CPE *Heavy galvanized steel, with baking varnish *Anti-ultraviolet, resist corrosion designed for durability in harsh environments	**8,9 €**
Media converter ottici			
WI-MC101M ***(venduti in coppia)***		* 25KM 100Mbps Single Fiber Optic Media Converter * Ambient temperature: 0 ~ +50°C Storage temperature: -20 ~ +70°C Humidity: 5% ~ 90% * Connector: UTP: RJ-45,10/100Mbps; Fiber: SC,100Mbps * Support Tag-VLAN,Port-VLANs * Supports up to 2k byte JUMBO frame * Power adapter 5V/1A included	**61,1 €**
WI-MC101G ***(venduti in coppia)***		* 25KM 1000Mbps Single Fiber Optic Media Converter * Ambient temperature: 0 ~ +50°C Storage temperature: -20 ~ +70°C Humidity: 5% ~ 90% * Connector: UTP: RJ-45,100/1000Mbps; Fiber: SC,1000Mbps * Support Tag-VLAN,Port-VLANs * Supports up to 9k byte JUMBO frame * Power adapter 5V/1A included	**109,2 €**
WI-MC111GP		* Gigabit PoE SFP Media Converter * 1 10/100/1000Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX * Connector: UTP: RJ-45,100/1000Mbps; Fiber: SFP,1000Mbps * RJ45 Port support 802.3af/at PoE output 30W * Complies with IEEE 802.3ab,IEEE 802.3af/at and IEEE 802.3z * Supports up to 9k byte JUMBO frame * FX port supports hot-swappable * Maximum transmission distance depends on the inserting SFP * Power adapter 48-52V/1A included	**83,3 €**
WI-MC111GP-O		* Gigabit SFP Outdoor Media Converter * 1 10/100/1000Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX * Connector: UTP: RJ-45,100/1000Mbps; Fiber: SFP,1000Mbps * RJ45 Port support 802.3af/at PoE output 30W * Complies with IEEE 802.3ab and IEEE 802.3z * Supports up to 9k byte JUMBO frame * FX port supports hot-swappable * Maximum transmission distance depends on the inserting SFP * DC Input 44-57V, not include the power adapter * IP65 Waterproof Design	**85,1 €**

Access Point Cloud da interno ed esterno			
WI-AP210		* 802.11N 2.4G 300Mbps Indoor Wireless Ceiling AP * Atheros chipset 128MB DDR2,16MB Flash,500mW High-Power,access 50users * 2*3.5dBi inside antenna * 2 x 100Mbps Ethernet port * 48V PoE Support,not include PoE adapter * Support hadware controller managed * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**81,4 €**
WI-AP210-Lite		* 802.11N 2.4G 300Mbps Indoor Wireless Ceiling AP * MTK chipset 64MB DDR2,8MB Flash,128mW High-Power,access 30users * 2*4dBi inside antenna * 2 x 100Mbps Ethernet port * 48V PoE Support,not include PoE adapter * Support hadware controller managed * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**66,6 €**
WI-AP216		* 802.11AC 2.4G&5.8G 1200Mbps Indoor Wireless Ceiling AP * 11AC Wave2 2.4GHz 300Mbps+5.8Ghz 867Mbps * MTK chipset 64MB DDR2, 8MB Flash, 200mW High-Power,access 48users * 2* 4.6 dBi (2.4G) + 2* 4dBi (5.8G) inside antenna * 2 x 100Mbps Ethernet port * 48V PoE Support,not include PoE adapter * Support hadware controller managed * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**85,1 €**
WI-AP217 V2		* Wi-Fi 5 1200M Indoor Wireless Ceiling AP * 11AC Wave2, 300Mbps on 2.4GHz+887Mbps on 5.8Ghz * Atheros chipset 128MB RAM, 16MB Flash, 200mW TX Power,access 150users * 4*5dB inside antenna * 48V PoE Support,2 x Gigabit Port, not include PoE adapter * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**181,4 €**
BEST SELLER **WI-AP217-Lite V2**		* Wi-Fi 5 1200M Indoor Wireless Ceiling AP * 11AC Wave2, 300Mbps on 2.4GHz+887Mbps on 5.8Ghz * MTK chipset 128MB RAM, 16MB Flash, 100mW High-Power,access 100users * 2.4GHz: 2 x 4.6dBi , 5GHz: 2 x 4dBi inside antenna * 802.3af PoE Support, 2 x Gigabit Port, not include PoE adapter * Support hardware controller managed * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**137,0 €**
BEST SELLER **WI-AP218AX V2**		* Wi-Fi 6 1775Mbps Indoor Wireless Ceiling AP * 574Mbps on 2.4 GHz and 1201Mbps on 5 GHz * Atheros chipset 512MB RAM, 128MB Flash, 200 mW TX Power,access 250users * 2.4GHz: 2 x 3dBi , 5GHz: 2 x 3dBi inside antenna * 802.3at PoE Support, 2 x Gigabit Port, not include PoE adapter * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**292,5 €**
BEST SELLER **WI-AP218AX-Lite V2**		* Wi-Fi 6 1775Mbps Indoor Wireless Ceiling AP * 574Mbps on 2.4 GHz and 1201Mbps on 5 GHz * MTK chipset 128MB RAM, 16MB Flash, 160mW TX Power,access 150users * 2.4GHz: 2 x 4.6dBi , 5GHz: 2 x 4dBi inside antenna * 802.3af PoE Support,2 x Gigabit Port, not include PoE adapter * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**162,9 €**
BEST SELLER **WI-AP219AX V2**		* Wi-Fi 6 5400Mbps Indoor Wireless Ceiling AP * High quality exterior design * 574Mbps on 2.4 GHz and 4800Mbps on 5 GHz * MTK chipset 512MB RAM, 128MB Flash, 160mW TX Power,access 256users * 2.4GHz: 2 x 4.6dBi , 5GHz: 2 x 4dBi inside antenna * 802.3at PoE Support, 1 x Gigabit Port and 1x 2.5G PoE in Port, not include PoE adapter * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**340,1 €**
WI-AP219AX-Lite V2		* Wi-Fi 6 3000Mbps Indoor Wireless Ceiling AP * High quality exterior design * 574Mbps on 2.4 GHz and 2402Mbps on 5 GHz * Qualcomm chipset 256MB RAM, 16MB Flash, 160mW TX Power,access 150users * 2.4GHz: 2 x 4.6dBi , 5GHz: 2 x 4dBi inside antenna * 802.3af PoE Support,2 x Gigabit Port, not include PoE adapter * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**187,2 €**

WI-AP416		* 802.11AC 2.4G&5.8G 1200M Indoor Wireless Inwall AP * 11AC Wave2 2.4GHz 300Mbps+5.8Ghz 867Mbps * MTK chipset 128MB DDR2, 16MB Flash, 100mW High-Power,access 50+users * 4*2dB inside antenna * 48V PoE Support,2 x 100Mbps Ethernet port, not include PoE adapter * Support hardware controller managed * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed	**81,4 €**
WI-AP417P		* Wi-Fi 5 1300Mbps Gigabit Wall-plate Wireless Access Point * WiFi 5 / 802.11ac standards. * 400Mbps on 2.4GHz and 867 Mbps on 5GHz, ultra-fast speed up to 1267Mbps transmission rate. * Full-gigabit port design and adapt to higher rate bandwidth. * Support PoE 802.af/at PD access and 802.af/at PoE output. * Support IPTV and VOIP data transmission, meeting the requirements for multi-service access. * Wall-plate panel design for easy deployment. * Support AP controller and cloud management	**144,4 €**
WI-AP310		* 802.11N 2.4G 300Mbps Outdoor Wireless AP * 11N 2.4GHz 300Mbps * Atheros chipset 64MB DDR2, 16MB Flash ,access up 50users+ * 2*5dBi external Omni antenna, 22dBm High-Power for 200 Meters LOS wireless cover range * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed * Support Qvlan binding multi-SSID * 2 x 100Mbps Ethernet port * 24V Passive PoE adapter included * IP65 rated, weather and dust sealed * Flexible wall or pole mounting options	**61,1 €**
WI-AP310-Lite		* 802.11N 2.4G 300Mbps Outdoor Wireless AP * 11N 2.4GHz 300Mbps * Support Mesh mode for easy connect each other via wireless * MTK chipset 64MB DDR2, 8MB Flash, ,access up 30users+ * 2*5dBi external Omni antenna,22dBm High-Power for 200 Meters LOS wireless cover range * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed * Support Qvlan binding multi-SSID * 2 x 100Mbps Ethernet port * 24V Passive PoE adapter included * IP65 rated, weather and dust sealed * Flexible wall or pole mounting options	**53,5 €**
WI-AP315		* 802.11AC 2.4G&5.8G 750Mbps Outdoor Wireless AP * 11AC 2.4GHz 300Mbps+5.8Ghz 443Mbps * Atheros chipset 128MB DDR2, 16MB Flash, 500mW High-Power for 400 Meters LOS wireless cover range ,access up 90users+ * 2*3.5 dBi (2.4G) +2*4 dBi (5.8G) inside Omni antenna * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed * Support Qvlan binding multi-SSID * 2 x 100Mbps Ethernet port * 802.3af PoE supported, poe adapter not included * IP65 rated, weather and dust sealed * Flexible wall or pole mounting options	**103,2 €**
WI-AP316		* 802.11AC 2.4G&5.8G 1200Mbps Outdoor Wireless AP * 11AC 2.4GHz 300Mbps+5.8Ghz 867Mbps * Support Mesh mode for easy connect each other via wireless * MTK chipset 64MB DDR2, 8MB Flash, ,access up 60users+ * 2*5dBi external Omni antenna,22dBm High-Power for 200 Meters LOS wireless cover range * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed * Support Qvlan binding multi-SSID * 2 x 100Mbps Ethernet port * 24V Passive PoE adapter included * IP65 rated, weather and dust sealed * Flexible wall or pole mounting options	**87,9 €**
WI-AP317		* 802.11AC 2.4G&5.8G 1200Mbps Outdoor Wireless AP * 11AC 2.4GHz 300Mbps+5.8Ghz 867Mbps * Atheros chipset 128MB DDR2, 16MB Flash, ,access up 250users+ * 4*5dBi inside Omni antenna,200mW High-Power for 200 Meters LOS wireless cover range * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed * Support Qvlan binding multi-SSID * 2 x 1000Mbps Ethernet port, * 802.3at PoE supported, poe adapter not included * IP65 rated, weather and dust sealed * Flexible wall or pole mounting options	**187,2 €**

WI-AP316AX		* Wi-Fi 6 3000Mbps Outdoor Cloud Wireless AP Qualcomm chipset 128MB DDR2, 16MB Flash, ,access up 250users+ * Ultra-Fast Wi-Fi 6 Speeds: Simultaneous 574Mbps on 2.4 GHz and 2402Mbps on 5 GHz totals 2976Mbps Wi-Fi speeds * 1 x Gigabit Ethernet (RJ-45)Port (supports IEEE 802.3af/at PoE) * 2.5 Gigabit (SFP) port for a lightning-fast user experience * IP67 rated, weather and dust sealed * Support AP controller and cloud management	**301,9 €**
WI-AP510		* 802.11AC 2.4G&5G 1200Mbps Outdoor Wireless AP * Dualband 2x2 1200Mbps 802.11ac Wave2 outdoor access point * Atheros chipset 128MB DDR2, 16MB Flash * 800 Meters LOS wireless cover range, up to 300+ users * Suport AP, Router,Repeater WISP mode * Support Qvlan binding multi-SSID * 1 x Gigabit Ethernet port, * 802.3at PoE supported, include Gigabit PoE Adapter * IP67 rated, weather and dust sealed * Flexible wall or pole mounting options * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed * included 2pcs 8dBi 2.4Ghz and 2pcs 12dBi 5.8Ghz Onmi dual-band antenna for 800 meterts coverage)	**412,7 €**
WI-AP518AX		* Ultra-Fast Wi-Fi 6 Speeds: Simultaneous 1148Mbps on 2.4 GHz and 2402Mbps on 5.8 GHz totals 3550Mbps Wi-Fi speeds * OFDMA and Uplink & Downlink MU-MIMO increase network capacity by up to 4× versus Wi-Fi 6 (802.11AX) in high-density environments to connect more devices simultaneously * Atheros chipset 1024MB DDR3, 128MB Flash, 200mW High-Power,access 500users * 1 x 2.5Gbps Ethernet port * 48V PoE Support, not include PoE adapter * IP67 rated, weather and dust sealed,Flexible wall or pole mounting options * Support QVLAN+SSID, Portal,AC controller Managed and Cloud Managed * included 4pcs 6dBi Onmi dual-band antenna for 600meterts coverage)	**611,4 €**
Controller Access point gestibile da Cloud e Gateway Gateway			
WI-AC500		* Wireless AP Controller with 6*2.5 Gigabit Ports(1× WAN + 4× WAN/LAN + 1× LAN) * Maximum AP managed number up to 500PCS * Support Multi-WAN load balance * WLAN Radio Spectrum Analysis to ensure work on best channel * Unified manage all indoor and outdoor Aps * Intra-AC, Inter-AP L2 roaming time less than 40ms * Built-in captive portal server and customerized welcome page * Support Cloud Managed	**955,3 €**
WI-AC150		* Wireless AP Controller with 5* Gigabit Ethernet Ports * Maximum AP managed number up to 150PCS * Support end users access 2000 * Support 1-4 WAN ports for load balance * WLAN Radio Spectrum Analysis to ensure work on best channel * Unified manage all indoor and outdoor Aps * Intra-AC, Inter-AP L2 roaming time less than 40ms * Built-in captive portal server and customerized welcome page * Support Cloud Managed	**305,7 €**
WI-AC105P V2		* 5 1000Mbps Ethernet ports. * 1 x WAN + 3 x WAN/LAN + 1 x LAN. * 4 Port PoE Out with 802.3af/at * Centralized management for 32APs * Support PPTP/L2TP/IPsec/OpenVPN	**133,7 €**
WI-AC108P V2		* 8 1000Mbps and 2 2.5G Ethernet ports. * 1 x WAN + 8 x LAN * 8 Port PoE Out with 802.3af/at * Centralized management for 64APs * Support PPTP/L2TP/IPsec/OpenVPN	**229,3 €**
WI-AC50		* Mini Wireless AP Controller with 2*100Mbps Ports(1PoE Input) * Maximum AP managed number up to 50PCS * Support by-pass mode only process AP control data * WLAN Radio Spectrum Analysis to ensure work on best channel * Unified manage all indoor and outdoor Aps * Intra-AC, Inter-AP L2 roaming time less than 40ms * Built-in captive portal server and customerized welcome page * Support Cloud Managed	**45,9 €**

Soluzioni Network ISP			
WI -NR3230		* 5G Indoor CPE with AX3000 * Release 15, Cat.19, Support SA and NSA * Quad Core 2GHz, 1GB DDR4, 1GB nand flash * SA Sub-6: DL 4.67Gbps,UL 1.25Mbps, NSA Sub-6: DL 4.47Gbps, UL 730Mbps * Wi-Fi 6 AX3000, 1 x 2.5GE WAN RJ45 Port +1x 2.5GE LAN RJ45 Port, 1xRJ11 Port * Support voip/volte/cs * Support TR-069	**573,2 €**
WI-NR3100		* 5G Outdoor CPE * Support SA and NSA, Release 16, Cat.19 * Quad Core 2GHz, 1GB DDR4, 1GB nand flash * SA Sub-6: 4.67Gbps (DL)/ 2.5Gbps (UL), NSA Sub-6:4.3.74Gbps (DL)/ 1.46GbpS (UL) * Support 1x 2.5GE LAN RJ45 Port * Support 802.3af PoE In * Support IP65 weatherproof * Support TR-069 * Included 1*Gigabit 48V PoE adapter in packing box	**764,3 €**
WI-MF5518		* 4G Portable MIFI * Support SA and NSA, Release 16 and Cat19 * Qualcomm chips, 1GB RAM, 1GB Flash * SA Sub-6 : DL 2.4Gbps; UL 900Mbps, NSA Sub-6: DL 3.2Gbps; UL 600Mbps * Wi-Fi 6 1800Mbps at 2.4GHz and 5GHz * 2.4 LCD colour touch screen, 5000mAh detachable battery * Included DC 5V 3A USB-C adapter in packing box	**649,6 €**
WI -GP1412		* AC1200 Dual Band Wi-Fi 5 GPON Router * Dual core 1GHz, 256MB RAM, 128MB Flash * GPON UP:1.25Gbps DOWN:2.5Gbps * 4 X GE LAN, 2 X RJ11 VOIP PORT * Wi-Fi 5 AC1200 (574Mbps@2.4Ghz, 2402Mbps@5GHz) * 2 x 5dBi external 2.4G antenna, 2 x 5dBi external 5.8G antenna * Support TR-069	**95,5 €**
WI-GP1430		* AX3000 Dual Band Wi-Fi 6 GPON Router * Dual core 1GHz, 512MB RAM, 256MB Flash * GPON UP:1.25Gbps DOWN:2.5Gbps * Wi-Fi 6 AX3000 (574Mbps@2.4GHz + 2402Mbps@5GHz) * 4 X GE LAN Ports, 2 X RJ11 VOIP Ports * 2 x 5dBi external 2.4G antenna, 2 x 5dBi external 5.8G antenna * Support USB3.0 * Support TR-069	**133,7 €**
WI-WR796-BE		* Wi-Fi 7 BE9600 Tri-band Wi-Fi Router * Broadcom chip, 512MB RAM, 256MB Flash * 1032Mbps@2.4Ghz, 2882Mbps@5GHz, 5764Mbps@6GHz * 1* 10GE WAN Port, 4* 1GE LAN Port, 1XRJ11(optional) * 3 x 3dBi Internal 2.4G antenna, 2 x 5dBi Internal 5.8G antenna, 2 x 5dBi Internal 6G antenna * Support USB3.0（optional), EesyMesh * Support TR-069	**420,4 €**
Antenne 6GHz PTP/PTMP			
WI-FW5625 ***(vendute in coppia)***	 * Palo NON incluso	* 6GHz PTP FWA AX2400 * Wi-Fi 6E, 5.925-7.125GHz, 2x2MU-MIMO/OFDMA * 1*2.5GE RJ45 Port + 1*GE RJ45 Port * 26dBm Max.Tx Power * Included External 25dBi Dish Antenna, Horizontal 8 degrees, vertical, 8 degrees * 802.3at PoE In on 2.5GE, or DC 12-48V * Support TR-069	**1.146,4 €**
WI-FW5620-H		* 6GHz PTMP FWA AX2400 * Wi-Fi 6E, 5.925-7.125GHz, 2x2 MU-MIMO/OFDMA * 1*2.5GE RJ45 Port + 1*GE RJ45 Port * 26dBm Max.Tx Power * Included External 20dBi Horn Antenna, Horizontal 30 degrees, vertical, 30 degrees * 802.3at PoE In on 2.5GE, or DC 12-48V * Support TR-069	**458,6 €**
WI-FW5600		* 6GHz PTMP FWA AX4800 * Wi-Fi 6E, 5.925-7.125GHz, 4x4 MU-MIMO/OFDMA * 1*2.5GE RJ45 Port + 1*GE RJ45 Port * 26dBm Max.Tx Power * 4*RPSMA (External antenna) * 802.3at PoE In on 2.5GE, or DC 12-48V * Support TR-069	**687,9 €**

Alimentatori da barra DIN			
MDR-60-48		AC/DC industrial rail Power Supply 48Vdc , 1,25A , 60W	**63,00**
NDR-120-48 **WI-DP120W-48V**		AC/DC industrial rail Power Supply 48Vdc , 2,50A , 120W	**86,00**
NDR-240-48 **WI-DP240W-48V**		AC/DC industrial rail Power Supply 48Vdc , 5,0A , 240W	**166,00**
NDR-480-48 **WI-DP480W-48V**		AC/DC industrial rail Power Supply 48Vdc , 10,0A , 480W	**275,00**
WI-DP30W-12V		AC input 100-240V 0,8A max - DC output 12V , 2,5A , 30W . Range di temperatura : -20°C/+70°C	**38,00**